

BITUMINOUS ALUMINIUM PAINT

**HEAT AND UV-REFLECTIVE COATING FOR ASPHALTIC,
BITUMEN, CONCRETE AND METALLIC SURFACES
MAINTENANCE COATING FOR BUILT-UP
WATERPROOFINGSYSTEMS**

TYPICAL PROPERTIES AT 25°C

PRODUCT DESCRIPTION:

As a decorative, reflective coating on all bituminous systems and roof repairs.

SPECIFICATION:

All surfaces to be coated with Pro-Struct 202 must be clean, sound and dry. All areas must be free from oils and grease.

INSTRUCTIONS:

Concrete and bituminous surfaces must be primed with Pro-Struct 201 Primer. Refer to product data sheets for preparation of surfaces. Apply by brush or roller.

MIXING:

Stir well. Aluminium flakes will settle and the product must be continuously stirred. Adequate ventilation must be allowed for and do not smoke or use naked flame during application.

CLEANING:

Clean equipment with Pro-Struct 105 Epoxy Brush Cleaner and rinse off with water.

Colour	Aluminium
Shelf Life	12 Months
Number of Components	1
Coverage	6 to 10m ² /litre/coat Recommend 2 coats
Flash Point	35°C
Consistency	Thin liquid
Drying Time	2 to 4 Hours
Solids % Mass	25%
Application	Brush, roller or spray
Application Temperature Range	10 to 35°C
Water Resistance	Not recommended for total Immersion
Solvent Resistance	Solvents will attack bitumen
VOC	625 g/l

Safety: Material is flammable and the necessary safety precautions need to be taken in the handling of this product.