

SELECTION & SPECIFICATION DATA

Generic Type	Single package high alkaline liquid degreaser.
Description	Carboclean 252 is a highly concentrated heavy alkaline cleaner for use through foam generating equipment, high pressure cleaner, steam cleaner, floor scrubber and immersion tanks. Very effective as a cold soak tank cleaner. Carboclean 252 is designed for use on concrete and ferrous metals only. NOTE: Ensure correct disposal of spent material.
Color	Light Amber
Theoretical Coverage Rates	10m ² /litre of ready to use solution NOTE: Material losses during mixing and application will vary and must be taken into consideration when estimating job requirements.

MIXING & THINNING

Mixing	For cleaning concrete floors using a foam generator or by manual brushing, dilute between 2% and 20%, depending upon the type and degree of soiling, i.e. add 2 litres to 10 litres water. For cleaning engines, chassis and under carriages using steam or high pressure washers, dilute Carboclean 252 to between 0.5% and 1.5% with water. For cleaning ferrous metals using a foam generator, dilute to 20% with water (1:4 parts).
---------------	---

APPLICATION EQUIPMENT GUIDELINES

Listed below are general equipment guidelines for the application of this product. Job site conditions may require modifications to these guidelines to achieve the desired results.

Spray Application	Use a foam generator as required.
Brush	Use a medium bristle brush for small areas and soft bristle brooms for large areas. Wash thoroughly with potable water to remove all Carboclean 252 prior to preparation and coating.

CLEANUP & SAFETY

Cleanup	Use water to clean up.
Safety	Carboclean 252 is highly alkaline and should be treated accordingly. Wear protective clothing when handling. In the event of contact with skin, flush immediately with water and diluted vinegar. Eye contact should be treated immediately by flushing with copious amounts of water prior to seeking medical attention.
Caution	Always mix in plastic containers, not metal. Always add Carboclean 252 to water, not vice versa.

PACKAGING, HANDLING & STORAGE

Shelf Life	24 Months minimum when stored at 25°C *Shelf Life: (actual stated shelf life) when kept at recommended storage conditions and in original unopened containers.
Shipping Weight (Approximate)	25 Litre Carboclean 252: 29 kg

Carboclean 252

PRODUCT DATA SHEET



PACKAGING, HANDLING & STORAGE

Storage Temperature & Humidity	4 to 65°C 0 to 100%
---	------------------------

Storage	Store indoors
----------------	---------------

WARRANTY

To the best of our knowledge the technical data contained herein is true and accurate on the date of publication and is subject to change without prior notice. User must contact Carboline Company to verify correctness before specifying or ordering. No guarantee of accuracy is given or implied. We guarantee our products to conform to Carboline quality control. We assume no responsibility for coverage, performance, injuries or damages resulting from use. Carbolines sole obligation, if any, is to replace or refund the purchase price of the Carboline product(s) proven to be defective, at Carbolines option. Carboline shall not be liable for any loss or damage. NO OTHER WARRANTY OR GUARANTEE OF ANY KIND IS MADE BY CARBOLINE, EXPRESS OR IMPLIED, STATUTORY, BY OPERATION OF LAW, OR OTHERWISE, INCLUDING MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. All of the trademarks referenced above are the property of Carboline International Corporation unless otherwise indicated.