

CRACK FILLER

**LIGHTWEIGHT
EASY TROWELLING
NON-SLUMPING
LONG OPEN TIME & MATCHES PLASTER FINISH**

PRINCIPAL USES

A tough flexible, low shrinkage crack filler suitable for filling in plaster, brick and concrete wall surfaces defects prior to coating. Major plaster defects can be made good with Pro-Struct 610 Mortarproof in accordance with Manufacturer's detailed instructions.

RESISTANCE

Once dry, the "Crack Filler" has excellent water and UV resistance and is unaffected by the cyclic temperature changes.

SPECIFICATION

All cracks and minor plaster defects to be made good with Pro-Struct 684/1 Crack Filler to Manufacturer's detailed instructions.

INSTRUCTIONS

All surfaces to be clean, dry and sound. Remove loose friable material from the cracks or holes. Fill and compact with "Crack Filler" by means of a putty knife or trowel. Smooth with dampened trowel. Alternatively, allow the Crack Filler to dry before sanding smooth with fine sandpaper.

TYPICAL PROPERTIES AT 25°C

Finish	Smoothed, trowelled plaster
Colour	Off-white
Type	Resin bound filler
Volume Solids	N/A
Theoretical Coverage per Coat	1m ² /lt at 1mm thick
Apply Over	Dust and oil-free masonry and wood surfaces
Apply By	Trowel, putty knife
Drying Time	1 Hours at 25°C
Thinner	Water
Shelf Life	12 Months
Application Temperature Range	10°C to 35°C