

**INTERIOR / EXTERIOR  
EASY APPLICATION – NON-DRIP SYSTEM  
EXCELLENT DURABILITY**

**PRINCIPAL USES**

A high quality wall and ceiling paint, ideal for redecorating previously painted surfaces, as well as coating new plaster, asbestos and concrete surfaces.

**RESISTANCE**

Good resistance to substrate alkali attack, severe weather conditions and general household detergent washing.

**INSTRUCTIONS**

All surfaces to be sound, clean and dry before application. On well adhering previously coated surfaces, a light sanding followed by thorough washing to remove dirt and dust prior to application is necessary. On freshly plastered surfaces, allow the plaster to dry out and remove dust before application.

If substrates are porous, it should be sealed with Pro-Struct 689 Alkali Resistant Plaster Primer prior to coating.

Apply two or three coats by brush, roller or airless spray at the following spread rates:

- Flat surfaces using a lambs-wool roller :  $\pm 8$  to  $10\text{m}^2/\text{litre}/\text{coat}$
- Rough irregular surface using brush, roller or airless spray :  $\pm 6$  to  $8\text{m}^2/\text{litre}/\text{coat}$

**GENERAL DATA SUMMARY**

Type	Copolymer Acrylic Paint
Finish	Smooth, matt
Colour	Brilliant White
Drying Time	3 to 4 hours at $25^\circ\text{C}$
Overcoat Time	4 Hours at $25^\circ\text{C}$
Spread Rate	$\pm 8$ to $10\text{m}^2/\text{litre}$ on flat surfaces
Application	Brush, roller or airless spray
Cleaner	Water